

Document scanning. Done right.™

The ImageTrac 5300 class scanners provide an efficient document scanning solution that helps organizations improve the productivity of their prep, scan and downstream processes by maximizing efficiencies and reducing exceptions -- all while delivering superior reliability.



The ImageTrac 5300 class scanners are designed for applications with moderate amounts of in-line processing and are available with either one or two out-sort pockets. The ImageTrac 5300 class scanners are ideal for a range of applications, including:

- Medical records scanning
- Mortgage processing
- Tax processing
- Claims processing
- Application processing
- Lockbox processing
- Back-file conversion
- Service bureau/shared services processing
- Digital mailroom

The ImageTrac 5300 class is available in two speed options. The ImageTrac 5350 provides duplex scanning (300 DPI) at up to 286 pages per minute and up to 429 pages per minute with the high speed option.*

In addition to providing high-quality, efficient processing at exceptional speeds, the ImageTrac 5300 class scanners also reduce document preparation cost by allowing for the scanning of documents of multiple sizes and thicknesses in a single pass. This means that document prep workers have fewer exceptions and steps to contend with in getting batches prepared for scanning.

The ImageTrac 5300 class scanners also provide dual multi-feed detection to help eliminate downstream errors. When a double-feed is detected, the ImageTrac scanning track automatically stops to allow for recovery. This doubles detection technology ensures that all pages are scanned and eliminates the need for operators to do a post-scan review to account for all images.

The ImageTrac 5300 has the ability to expand and be upgraded to the 5400 class scanner. This assures that if your needs change or operation grows so can your ImageTrac.

BENEFITS:

- Reduced document preparation
- Fewer jams/fast jam recovery
- Increased operator productivity
- Reduced operations expense
- Less downtime/easy maintenance
- Fewer downstream exceptions
- Potential to finish scan work earlier in the day
- Ergonomically enhanced

FEATURES:

- Throughput speeds of 286 pages per minute and 429 ppm with the high speed option*
- Duplex camera imaging
- Mixed document scanning
- Bi-tonal, grayscale and color scanning
- DynamicTIFF
- Ultrasonic doubles detection
- Multi-feed detection
- Mechanical document detection and de-skew
- Single pocket
- User-friendly touch screen control

OPTIONS:

- Single pocket with run-out tray
- Additional sort pocket
- Thick document
- Envelope detection
- Hardware barcode reader
- Pre- and post-image ink jet printer
- Hardware MICR reader
- Up to 21 pockets
- JPEG 2000
- DocNetics® suite

The ImageTrac 5300 class scanners are powered by ibml's proven SoftTrac Scan capture software for improved operational control, scanning accuracy and document processing. Built for the shared services approach, SoftTrac Scan allows operators to manage scanning activities from an easy-to-use touch screen. It also provides the ability to manage scanning activities from a single console.

*Based on 8.5" x 11" documents with a 2" gap at 200 DPI.

ImageTrac 5300 Class Specifications

RATED THROUGHPUT SPEEDS IN LANDSCAPE ORIENTATION

MODEL	RESOLUTION DPI	8.5X11 IN. PAGES/MINUTE	A4 PAGES/MINUTE	CHECKS PAGES/MINUTE	A6 PAGES/MINUTE
5350	300	286	292	632	489
High Speed Option	200	429	438	947	733

MAXIMUM DOCUMENT SIZE	297 mm [11.7 in.] x 432 mm [17 in.]
MINIMUM DOCUMENT SIZE	64 mm [2.5 in.] x 85 mm [3.25 in.]
PAPER THICKNESS AND WEIGHT	Standard feeder 45 g/m ² to 200 g/m ² ; Asian paper (rice paper) to card stock
FEEDER CAPACITY	1,500 sheets [20# bond paper]

OPTIONS		IMAGETRAC 5300
HARDWARE	BARCODE READER	Yes
	PATCH CODE READER	Yes
	SINGLE HEAD INK JET PRINTER	Pre and/or Post-Image
	MULTI-HEAD INK JET PRINTER	Pre-Image
	MICR - E13B	Yes
	MICR - CMC7	Yes
	SORT POCKETS	Single pocket with run-out tray; One additional sort pocket [Available on single pocket with run-out only.]
SOFTWARE	SOFTTRAC SCAN	Yes
	DOCNETICS SUITE	Yes

CERTIFICATIONS	
SAFETY	Standard for Information Technology Equipment, ANSI/UL 60950-1 First Edition, Dated April 1, 2003 (including revisions up to November 26, 2003) & CAN/CSA C22.2 No. 60950-1-03 First edition, EN 60950-1:2006 Second Edition, Information technology equipment - Safety [EN 60950-1:2006, A1:2009 + A11:2009], CE, Section 508.
EMISSIONS	CISPR 22 [Ed.3]: 1997 +A1 [EN55022: 1998 +A1], CISPR 24 [Ed.1]: 1997 +A1, A2 [EN 55024:1998 + A1, +A2], AS/NZS CISPR 22, AS/NZS CISPR 24, IEC 61000-3-2 [Ed.3]:2005, +A1, A2 [EN61000-3-2:2006], IEC 61000-3-3 [Ed.2]:2008 [EN 61000-3-3:1995 +A1, +A2, FCC 47CFR Part 15 Subpart B:2007, ICES-003:2004, VCCI V-3/2010.04, CNS 13438:1997.

FEATURES		
MULTI-FEED DETECTION	Single or multiple ultrasonic sensor technology and/or friction multi-feed detection	
COLOR TOUCH SCREEN CONTROL	Operator control via 21.5" wide screen color LCD panel touch screen	
ILLUMINATION	Dual LED illumination patented technology	
FILE FORMAT OUTPUT	JPEG (color/gray scale images); TIFF (black and white images); JPEG 2000	
RESOLUTION	OPTICAL	300 dpi
	OUTPUT	Black and White/Color/Gray scale: 100 to 600 dpi; Scaling range limited to 1/2x to 2x from optical camera dpi.
IMAGE PROCESSING	DynamicTIFF Thresholding; Speckle Removal; Auto crop; Auto-Deskew; Image Rotation; Multi-image Output; Color Dropout, etc.	
ENVIRONMENTAL FACTORS	RoHS compliant	
ACOUSTICAL NOISE	Operating mode 77.4db(A)	
HEAT DISSIPATION	6,000 to 15,000 BTUs/hour	
OPERATING HUMIDITY	20% to 80% non-condensing (percent relative humidity)	
OPERATING TEMPERATURE	50 to 90 degrees (F), 10 to 32 degrees (C)	
SHIPPING/STORAGE TEMPERATURE	-22 to 140 degrees (F), -30 to 60 degrees (C)	
ALTITUDE	Sea level to 10,000 ft (3,048 M)	
ELECTRICAL REQUIREMENTS	United States: 208V~, 2 Wire + GND25A 50/60 Hz; European Union: 230V~, 1 Wire + PE (single phase) 25A 50/60 Hz; Japan: 200V~, 2 Wire + GND25A 50/60 Hz <i>US Sites - Units shipped with power cord and 208-240V, NEMA #L6-30 connector</i> <i>Non US sites - Power cable supplied by customer to meet local electrical code</i>	
MACHINE DIMENSIONS	Width: 32.38; Length: 97.98 inches; Height: 48.33 inches Dimensions are for a 3 frame scanner; additional frames will vary the length.	
WEIGHT	Feeder frame: 226 lbs; Front camera frame: 284 lbs; Pocket frame: 235 lbs	
HOST	Embedded Application Controller	

Specifications are subject to change without notice.
Minimum gap and throughput will vary based on the specific application processing requirements.