

Features

- Two sort trays
- Throughput speeds of up to 150 pages per minute (PPM)
- Duplex camera imaging at 50 to 600 DPI output resolution
- Ultrasonic multi-feed detection
- Document Imprinter (front)
- Color Dropout
- Mixed document scanning
- Bi-tonal, grayscale and color scanning
- Left-justified feeding
- User-friendly touch screen control*



Software Options

- ImageTracDS software bundle
- SoftTrac® Capture Suite - additional modules
- DocNetics®
- Connectors for Kofax Capture, TiS eFlow, EMC Captiva

| SCANNER FEATURES | | |
|---|----------------|---|
| DUAL OUTPUT TRAYS | | # 1 - 550 sheets # 2 - 100 sheets |
| FEEDER TRAY (ADF) | | 550 sheets – left-justified feeder |
| MULTI-FEED DETECTION | | Ultrasonic |
| DOCUMENT IMPRINTER - SINGLE HEAD, POST IMAGE | | Front, 36 characters max. |
| ILLUMINATION | | Fluorescent |
| PAPER SIZE | MAXIMUM | 16.5 inches x 12 inches |
| | MINIMUM | 2.9 inches x 2.9 inches |
| PAPER THICKNESS | | 41 – 174 g/m2 (11 – 46 lbs) |
| DUTY CYCLE | | 150,000 pages per day |
| SUPPORTED DRIVERS | | TWAIN |
| IMAGE CAPTURE & OUTPUT | | |
| SIMPLEX AND DUPLEX CAPTURE | | 24 bit color |
| RESOLUTION | OPTICAL | 600 dpi |
| | OUTPUT | 50 – 600 dpi. Bitonal, Grayscale, Color |
| FILE FORMAT OUTPUT | | JPEG, TIFF |
| COLOR DROPOUT | | Single color - red, green or blue All colors - (only black remains) Custom - user defined |
| THROUGHPUT – PPM** | | Up to 150 PPM **approximate PPM for 8.5 x 11 at 200 dpi, landscape orientation |

*Requires touch-screen monitor, sold separately

| PC AND OPERATING SYSTEM REQUIREMENTS | |
|--------------------------------------|--|
| CPU | Intel processor, 3.4 GHz, Core i7 2600 or above |
| MEMORY | 4 GB 1333 MHz or faster |
| UNUSED HARD DISK SPACE | 10 GB or more |
| INTERFACE | USB 3.0 Port on PCIe, Gen 2 Slot or equivalent embedded on motherboard - Directly connect the device to the PC. Connection through a USB HUB is not supported. - Use the USB cable (For 3.0) inside the package sent with the device. Use of other cables may not guarantee maximum performance. |
| SUPPORTED OPERATING SYSTEM | Windows® 7 Professional, 64 bit |
| CERTIFICATIONS | |
| SAFETY | IEC/EN 60950-1:2005 (Second Edition), UL 60950-1:2007, CAN/CSA-C22.2 No. 60950-1-07 |
| EMISSIONS | CISPR22(2003): [EN55022(2006)A1(2007) Class A, EN61000-3-2(2006), EN61000-3-3(2008), EN55024(1998)A1(2001)A2(2003), ICES-003 Issue.4(2004.2)], FCC Part 15.107 (2008.7) Class A, FCC Part 15.109 (2008.7) Class A, |
| ADDITIONAL INFORMATION | |
| DIMENSIONS | 27.5 inches L x 19 inches W x 16 inches H |
| WEIGHT | 110 lb |
| POWER REQUIREMENTS | 100 – 240VAC, 4.0A, 50/60Hz |
| ENVIRONMENTAL FACTORS | RoHS2 Directive 2011/65/EU-EN50581, Energy Star |
| OPERATING TEMPERATURES | 50 to 95 degrees (F), 10 to 35 degrees (C) |
| OPERATING HUMIDITY | 35% to 70% non-condensing (percent relative humidity) |
| SHIPPING/STORAGE TEMPERATURES | -14 to 109 degrees (F), -10 to 43 degrees (C) |